

Applications

Designed to remove and contain oily water from a waste water system.

Toxicity and handling

Bioassay information is available upon request.

Handle as an industrial chemical, wearing protective equipment and observing precautions described in the safety datasheet.

Packaging and storage

ICMC OWS clay is packaged in 50lb and/or 25kg multiwall, paper sacks or 500kg/1000kg nett big bags

Store in a dry, well-ventilated area. Keep container closed. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping, or stacking.

Typical Physical Properties

Item	Granular Size	Specification	Tolerance
1	< 4.0 mm	5%	Max 5%
2	> 0.355 mm	5%	Max 5%

Item	LOI	Specification	Tolerance
3	39.0	TPI 142	+/- 1.5%

Tested Acceptable Criteria

Item	Granular Size	Specification	Tolerance
1	< 4.0 mm	2.5% (5%)	Max 5%
2	< 2.8 mm	15%	10 - 25%
3	< 1.7 mm	30%	25 - 40%
4	< 1.4 mm	10%	10 - 20%
5	< 1.0 mm	20%	10 - 25%
6	< 0.355 mm	20%	10 - 25%
7	> 0.355 mm	2.5% (0%)	Max 5%
8	Midpoint (1+2+3+4)	57.5% (60%)	50% - 70%

Item	LOI	Specification	Tolerance
9	39.0	TPI 142	+/- 1.5%

All specifications are subject to change without notice.